

Monarfloor® Flanking Band

Acoustic band designed to reduce impact sound transmission through and under party walls

INTENDED USE

BMI Monarfloor® Flanking Band isolates party and flanking walls reducing both impact vibration transmission from the floor and the flanking sound transmission path within the building. Intended for use with Monarfloor acoustic floating floors, and other Second Generation systems.

INSTALLATION SUMMARY

- Ensure the sub-floor and walls are suitably prepared.
- Flank all perimeter with Monarfloor® Flanking Band.
- Butt the acoustic flooring treatment tight to the Monarfloor® Flanking Band.
- After installing the acoustic flooring system, install skirting and trim off excess Flanking Band.

For full details refer to our Monarfloor® Flanking Band Installation Guide.

SAFETY, QUALITY & ENVIRONMENT

BMI Icopal products are distributed under a Quality Management System approved to ISO 9001: 2015 and an Environmental Management System approved to ISO 14001: 2015, by TÜV NORD CERT GmbH.

Information regarding transportation, handling, storage and disposal can be found on the relevant Safety Data Sheet.



ISO 9001:2015
44 100 21410102



ISO 14001:2015
44 100 21410102

TECHNICAL SERVICES

For further information and technical support, please contact our technical services team.

T: +44 (0)330 123 4585

E: technical.uk@bmgroupp.com

PRODUCT DATA

Roll size	Product Code	Thickness
30mm x 25mm x 10m (90 degree angled)	20000156	6mm
75mm x 10m	20000149	6mm
150mm x 10m	20000155	6mm
250mm x 10m	20000265	6mm
300mm x 10m	20000275	6mm

Other sizes available as a special order - minimum order quantities apply.

CONSTRUCTION

Composition Flexible polyurethane foam

