

Sealoflex Endura BT System

Sealoflex Endura BT System is a 3-component, pigmented resin compound with a polymethyl methacrylate (PMMA) base.

INTENDED USE

Sealoflex Endura BT System is a self levelling compound used to receive surface layers in balcony and roof terrace waterproofing.

DESCRIPTION

Sealoflex Endura BT System is an exceptionally fast curing, cold liquid applied surfacing layer comprising resin, filler and catalyst.

INSTALLATION SUMMARY

Before applying Endura BT Resin System ensure that the surface is clean, dry and sound. Endura BT Resin System is a three component system comprising resin, filler and catalyst.

Do not apply if rain is imminent.

For detailed application instructions, mixing ratios and surface preparation, refer to the Sealoflex Endura Installation Guide, I.or contact BMI Icopal Technical Services for further advice.

PRODUCT DATA

Container size	Resin: 10 kg (drum) Filler: 23 kg (bag)
Form	Liquid
Application rate	Resin: 1.25kg/m ² Filler: 2.75kg/m ²
Consumption rate	Min. 4 kg per m ² (when mixed)
Rainproof	Approx. 30 minutes*
Walkable	Approx. 1 hour*
Overcoating period	Approx. 1 hour*
Withstand stress	Approx. 2 hours*
Pot Life	15 minutes
Shelf Life	6 months**
Colour	Buff

* Times given are reduced with higher (and increased with lower surrounding and work surface temperatures. Values attained at 20 °C.

** If stored in original container

CLEANING

Clean tools immediately after use with Sealoflex Endura Cleaner. Wash hands thoroughly after use.

STORAGE

Can be stored unopened and unmixed for approximately 6 months in a cool, dry place above freezing. Keep container away from direct sunlight when in storage and on the construction site.

TECHNICAL SERVICES

For further information and technical support, please contact our technical services team:

T: +44 (0) 330 123 4585

E: technical.uk@bmigroup.com

CERTIFICATION

Sealoflex Endura BT System has been independently site and laboratory tested by the British Board of Agrément, and awarded BBA certificate number 20/5753.



SAFETY, QUALITY & ENVIRONMENT

BMI Sealoflex products are manufactured under a Quality Management System approved to ISO 9001: 2015 and an Environmental Management System approved to ISO 14001: 2015, by TÜV NORD CERT GmbH.

Information regarding transportation, handling, storage and disposal can be found on the Safety Data Sheets.



ISO 9001:2015
44 100 21410102



ISO 14001:2015
44 100 21410102



BMI Group UK Limited

BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW
bmigroup.com/uk

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact BMI Icopal technical services team.