

# Sealoflex Ultima Coloured Quartz

Sealoflex Ultima Coloured Quartz consists of kiln dried silica granules. It is a component of the Sealoflex Ultima Anti-skid Walkway System.

## INTENDED USE

Sealoflex Ultima Coloured Quartz is used to create a hard wearing anti-skid surface above the primary waterproof coating. Sealoflex Ultima Coloured Quartz is an ideal solution where access for maintenance is required.

## INSTALLATION SUMMARY

Allow the Sealoflex Ultima waterproofing system to fully cure before beginning application of the anti-skid walkway system.

Once cured, apply a further coat of Sealoflex Ultima Waterproof Coating at a rate of 0.2 litres per m<sup>2</sup>. This provides a base resin layer to receive the Sealoflex Ultima Coloured Quartz.

Broadcast the Sealoflex Ultima Coloured Quartz by hand into the resin layer while it is still wet. Ample quantities of the quartz sand should be applied into the receiving resin to ensure full embedment of the granules. Once the granules and receiving resin have sufficiently cured, the excess granules can be swept off, collected and re-used prior to sealing with the Sealoflex Ultima Wearcoat Clear.

Personal Protective Equipment (PPE) should be worn.

## STORAGE

Product should be stored in a dry and cool environment.

## DISPOSAL

Solid EWC 19 12 09

## TECHNICAL SERVICES

For further information and technical support, please contact our technical services team:

T: +44 (0) 330 123 4585

E: [technical.uk@bmigroup.com](mailto:technical.uk@bmigroup.com)

## PRODUCT DATA

Container size	25 kg
Form	Solid / granular
Size	0.4 – 0.8 mm
Application rate	Approx. 3 - 5 kg per m <sup>2</sup>
Colour	Black and light grey granule mix

## CERTIFICATION

Sealoflex Ultima Bitumen Primer has been independently site and laboratory tested by the British Board of Agrément, and awarded BBA certificate number 15/5229.



## SAFETY, QUALITY & ENVIRONMENT

BMI Sealoflex primers are manufactured under a Quality Management System approved to ISO 9001: 2015 and an Environmental Management System approved to ISO 14001: 2015, by TÜV NORD CERT GmbH.

Information regarding transportation, handling, storage and disposal can be found on the Safety Data Sheets.



ISO 9001:2015  
44 100 21410102



ISO 14001:2015  
44 100 21410102

## BMI Group UK Limited

BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW  
[bmigroup.com/uk](http://bmigroup.com/uk)

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact BMI Icopal technical services team.