

Sealoflex Ultima TPO Primer

Sealoflex Ultima TPO Primer is a single component, solvent-based, low viscosity primer. It is a component of the Sealoflex Ultima System.

INTENDED USE

To promote adhesion of Sealoflex Ultima Waterproof Coating onto TPO /FPO synthetic membranes.

Please note: An adhesion test is required for installations onto this type of membrane.

SURFACE PREPARATION

Before applying Sealoflex Ultima TPO Primer ensure that the surface is clean, dry and sound. The surface temperature must be between 5 °C and 35°C and 3° C above the dew point. (Refer to the Dew Point Calculation Table in the Sealoflex Ultima Installation Manual).

Do not apply if rain is imminent.

INSTALLATION SUMMARY

1. This solvent based primer does not require mixing.
2. Apply product to the substrate using a roller or a brush.
3. The minimum consumption is 0.1 litre / m².
4. Allow primer to dry thoroughly before applying Sealoflex Ultima Waterproof Coating.
5. Clean tools in solvent immediately after use.

Please note: Sealoflex Ultima Waterproof Coating must be applied to the primed surface within 48 hours of application. If left longer, the surface must be re-primed.

STORAGE

Store the product at temperatures between 5°C and 35°C. Store containers on a level surface. Do not expose to direct sunlight. Keep away from sources of ignition. Do not expose to rainfall.

TECHNICAL SERVICES

For further information and technical support, please contact our technical services team:

T: +44 (0) 330 123 4585

E: technical.uk@bmigroup.com

PRODUCT DATA

Container size	1 litre
Form	Liquid
Consumption	0.1 litres per m ² *
Surface temperature limits	Between 5° C and 35° C (and 3° C above the dew point)
Drying time	15 minutes*
Shelf life	12 months**
Colour	Transparent

* At 23 °C and 50% relative humidity.

** If stored in original container between 5° C and 35° C.

CERTIFICATION

Sealoflex Ultima has been independently site and laboratory tested by the British Board of Agrément, and awarded BBA certificate number 15/5229.



SAFETY, QUALITY & ENVIRONMENT

BMI Sealoflex primers are manufactured under a Quality Management System approved to ISO 9001: 2015 and an Environmental Management System approved to ISO 14001: 2015, by TÜV NORD CERT GmbH.

Information regarding transportation, handling, storage and disposal can be found on the Safety Data Sheets.



ISO 9001:2015
44 100 21410102



ISO 14001:2015
44 100 21410102

BMI Group UK Limited

BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW
bmigroup.com/uk

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact BMI Icopal technical services team.