

# Sealoflex Ultima Wearcoat Clear

Sealoflex Ultima Wearcoat Clear is a single component, UV-resistant, protective coating. It is a component of the Sealoflex Ultima Anti-skid Walkway System.

## INTENDED USE

Sealoflex Ultima Wearcoat Clear forms part of the Sealoflex Ultima Anti-skid Walkway System and is used as a final encapsulation and UV protection layer above the embedded Sealoflex Ultima Quartz.

## SURFACE PREPARATION

Before applying Ultima Wearcoat Clear ensure that there are no loose Quartz granules on the surface and that it is clean and dry.

The surface temperature must be above 5° C and 3° C above the dew point. (Refer to the Dew Point Calculation Table in the Sealoflex Ultima Installation Manual). Do not apply if rain is imminent.

## INSTALLATION SUMMARY

1. Remove the lid of the container and stir product with a mixing stick or a mechanical mixer at low speed until it has reached an even consistency.
2. Apply product to the Quartz surface using a roller or a brush.
3. Coverage rate of 0.3 l/m<sup>2</sup> applied in one coat.
4. Clean tools in water immediately after use

**Please note:** Sealoflex Ultima Wearcoat Clear is milky white when applied. As it dries it becomes transparent, giving the surface a 'shiny' appearance. If the 'shine' is not visible apply a further coat, wait for it to dry and check the surface.

## PRODUCT DATA

<b>Container size</b>	4 litre and 20 litre
<b>Form</b>	Liquid
<b>Consumption</b>	0.3 l/m <sup>2</sup> *
<b>Surface temperature limits</b>	Above 5° C (and 3° C above the dew point)

\* On smooth surfaces.

## CURING BEHAVIOUR

<b>Pot life / workability period</b>	60 minutes*
<b>Rainproof</b>	20 minutes*
<b>Walkable / re-coat</b>	30 minutes*
<b>Shelf life</b>	12 months**
<b>Colour</b>	Milky white

\* At 23 °C and 50% relative humidity.

\*\* From date of manufacture in original unopened containers stored between 5° C and 35° C.

## STORAGE

Store the product at temperatures between 5°C and 35°C. Where the product is exposed to temperatures below 5°C, ensure duration of exposure is no greater than 5 days. For optimum usage it is recommended to maintain the material above 15°C overnight prior to use.

**Materials should not be exposed to freezing conditions**, as this will result in the products being unusable. Store indoors, away from direct sunlight.

## TECHNICAL SERVICES

For further information and technical support, please contact our technical services team:

**T:** +44 (0) 330 123 4585

**E:** [technical.uk@bmigroup.com](mailto:technical.uk@bmigroup.com)

## CERTIFICATION

BMI Sealoflex Ultima has been independently site and laboratory tested by the British Board of Agrément, and awarded BBA certificate number 15/5229.



## SAFETY, QUALITY & ENVIRONMENT

BMI Sealoflex Ultima Wearcoat Clear is manufactured under a Quality Management System approved to ISO 9001: 2015 and an Environmental Management System approved to ISO 14001: 2015, by TÜV NORD CERT GmbH.

Information regarding transportation, handling, storage and disposal can be found on the Safety Data Sheets.



ISO 9001:2015  
44 100 21410102



ISO 14001:2015  
44 100 21410102



## BMI Group UK Limited

BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW  
[bmigroup.com/uk](http://bmigroup.com/uk)

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact BMI Icopal technical services team.