

Declaration of Performance

No.: RED_DOPCE_2303_10002797

DIVOROLL ELITE 200

1. UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

Divoroll Elite 200 - 540272

2. INTENDED USE

Underlays for discontinuous roofing

3. MANUFACTURER

BMI Deutschland GmbH, Scharpenbergerstr.
72-90, 58256 Ennepetal, Germany

4. AUTHORISED REPRESENTATIVE, if applicable

BMI Group UK Limited, BMI House, 2 Pitfield, Kiln
Farm, Milton Keynes MK11 3LW

5. SYSTEM OR SYSTEMS AVCP

System 3

6. a) HARMONISED STANDARD or ETA

EN 13859-1/2: 2010

b) DESIGNATED STANDARD AND APPROVED BODY(IES)

DE - 0751 / 0761

Signed for and on behalf of the manufacturer by:

Lubini Nabutola, Director



At BMI House, Milton Keynes
on 20/03/2023

7. DECLARED PERFORMANCE

Essential Characteristics	Performance	Harmonised technical specification
Reaction to fire (EN 13501-1)	E-Class	EN 13859-1/-2: 2010
Resistance to water penetration (EN 1928)	W1	
Tensile strength (N/50mm) MD (EN 12311-1)	500 +/- 30N/5cm	
Tensile strength (N/50mm) CD (EN 12311-1)	480 +/- 30N/5cm	
Elongation MD/CD (%) (EN 12311-1)	20/15 (+/-5)	
Elongation after ageing MD/CD (%) (EN 12311-1)	15/10 (+/-5)	
Resistance to tearing (N) (nail shank) MD (EN 12311-1)	400 +/- 30N	
Resistance to tearing (N) (nail shank) CD (EN 12311-1)	400 +/- 30N	
Pliability (EN 1109)	-25° C	
Tensile strength after ageing (N/50mm) MD (EN 12311-1)	>325N/5cm	
Tensile strength after ageing (N/50mm) CD (EN 12311-1)	>315N/5cm	
Resistance to water penetration after ageing (EN 1928)	W1	

The performance of the product identified in points 1 and 2 is in conformity with the set of declared performance/s in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.