

Declaration of Performance

ICO_DOPCE_2210_00000000000310

Xtra-Load Diamond

1. UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

Xtra-Load Diamond

2. INTENDED USE

For damp proofing in buildings

3. MANUFACTURER, and, if applicable, AUTHORIZED REPRESENTATIVE

BMI Group UK Limited, BMI House,
2 Pitfield, Kiln Farm, Milton Keynes MK11 3LW

Necoflex Ltd. Matheson, Block a Riverside Iv, 70 Sir
John Rogerson's Quay, Dublin 2, Ireland

4. SYSTEM OR SYSTEMS AVCP

System 2 +

5. HARMONIZED STANDARD or ETA

BS EN 13967: 2012

6. NOTIFIED BODY(IES)

836

Signed for and on behalf of the manufacturer by:

Lubini Nabutola, Director



At BMI House, Milton Keynes

on 21/03/2023

7. DECLARED PERFORMANCE

Essential Characteristics	Performance	Harmonized technical specification
Reaction to Fire EN13501-1: 2018	NPD	BS EN 13967: 2012
Watertightness EN 1928 at 2 kPa	Pass	
Resistance to tearing (nail shank) EN 1928	NPD	
Joint Strength EN 12317-2	NPD	
Resistance to Impact EN 12691	NPD	
Tensile properties - reinforced sheets EN 12311-2 (Method A)	NPD	
Resistance to static loading EN 12730 (Method B)	NPD	
Durability - against ageing/degradation EN 1296 & EN 1928 (Method A 2 kPa)	Pass	
Durability - against chemicals EN 1847 & EN 1928 ((Method A 2 kPa)	Pass	
Dangerous substances No relevant standard	NPD	

NPD: No performance determined

*in acc. with Commission Decision 2000/553/EC

**in acc. with Commission Decision 96/603/EC

The performance of the product identified in points 1 and 2 is in conformity with the set of declared performance/s in point 7. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.