


Mono PR

1-LAYER WATERPROOFING BITUMEN MEMBRANE

Mono PR is a bitumen membrane well adapted to the harsch Swedish climate.

Product data	
Dimensioner	1x7,5 m, 1x6 m
Colour	Grey
Weight per m ²	5500 g
Weight per roll	41 kg
Transport unit	20 rolls per pallet

For additional information, see DoP 010-1510



Description

Mono PR, SEP 5500, is built around a strong polyester/glass reinforcement, impregnated and coated with SBS-modified bitumen on both sides. The underside is coated with easily activated, grooved patterned asphalt which makes it easy to weld, and which is protected by a thin plastic film which is melted in connection with the welding. The top side is coated with slate granules. The products are slate-free along one 12 cm edge to facilitate welding of longitudinal joints and there is also a marking for the location of the fasteners. Mono PR meets waterproofing class TKY-B-0034 and the fire requirements according to BROOF (t2).

Function

The waterproofing product must withstand the mechanical stress which the waterproofing layer is subjected to on the roof. Mono PR fits solid substrates and roof constructions. The membrane must be mounted by mechanical fastening and joint welding or string and joint welding.

Storage

The material is delivered standing on a disposable pallet. Keep the rolls upright and protected from moisture and direct sunlight.