

# Siplast Primer

Siplast Primer is a low viscosity priming solution consisting of elastomeric bitumen and hydrocarbon solvent.

## INTENDED USE

Siplast Primer is designed to penetrate and seal substrates of masonry, concrete, cementitious screeds or renders, existing bituminous or asphalt waterproofing, structural steelwork and other metals, prior to the application of bituminous membranes. Products should be installed in accordance with the manufacturer's installation guidelines.

## STORAGE

Siplast Primer is supplied in 25 litre metal buckets. The product must be stored under cover on a flat, level, and clean surface away from sources of ignition, including pilot lights and sparks. Keep containers tightly closed when not in use. In original unopened containers the shelf life is 12 months.

## INSTALLATION SUMMARY

Apply Siplast Primer by brush or roller ensuring the primer is well applied to the surface while avoiding pooling of the primer. Ensure the substrate is structurally sound, free of surface laitance, oils, grease, dirt, moss, lichen, and loose material. The surface should be smooth and free from sharp projections and loose debris, and any material which would hinder adhesion.

The product is to be installed in accordance with the manufacturer's instructions and current and relevant guidance documents.

For further details please consult our Flat Roofing Product Installation Guidelines or contact our technical services team.

## PRODUCT DATA

|                                   |                                     |
|-----------------------------------|-------------------------------------|
| Colour                            | Black                               |
| Coverage Rate <sup>(1)</sup>      | 3 – 11 m <sup>2</sup> per litre     |
| Application Rate <sup>(1)</sup>   | 0.1 – 0.3 litres per m <sup>2</sup> |
| Drying Time <sup>(2)</sup>        | 1 to 3 hours                        |
| Application Limits <sup>(3)</sup> | +5°C to +30°C                       |
| Container Size                    | 25L                                 |

(1) Depending on substrate porosity

(2) Depending on ambient temperature

(3) Surfaces must be free of ice and water

## PACKAGING

| Description    | Container Size | Product Code    |
|----------------|----------------|-----------------|
| Siplast Primer | 25L            | <b>10001450</b> |

## SAFETY, QUALITY & ENVIRONMENT

BMI Icopal products are manufactured under a Quality Management System approved to ISO 9001: 2015 and an Environmental Management System approved to ISO 14001: 2015, by TÜV NORD CERT GmbH.

Information regarding transportation, handling, storage and disposal can be found on the relevant Safety Data Sheet.

## TECHNICAL SERVICES

For further information and technical support, please contact our technical services team:

**T:** +44 (0) 330 123 4585

**E:** [technical.uk@bmigroup.com](mailto:technical.uk@bmigroup.com)



ISO 9001:2015  
44 100 21410102



ISO 14001:2015  
44 100 21410102



### BMI Group UK Limited

BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW  
[bmigroup.com/uk](http://bmigroup.com/uk)

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact our BMI Icopal technical services team.