

TorchSafe TA VCL Stripes

TorchSafe TA VCL Stripes is a glass reinforced SBS-modified bitumen membrane with bitumen bonding stripes on the upper surface.

APPLICATION

TorchSafe TA VCL Stripes is intended for use as an air & vapour control layer in a warm roof system build-up. Membranes should be installed in accordance with the manufacturer's guidelines.

Upper Surface	Silica sand with SBS-modified bitumen stripes with thermofusible film
Lower Surface	Heat-activated self-adhesive SBS-modified bitumen with release sheet
Material	SBS-modified bitumen
Type of Reinforcement	Glass 80g/m ²

Characteristic	Test Method	Value or Statement	Tolerance	Units
Length	BS EN 1848-1	7.5	≥ 7.5	m
Width (inc. Selvedge)	BS EN 1848-1	1	≥ 1.0	m
Straightness	BS EN 1848-1	<20	-	mm/10m
Mass per unit area	BS EN 1849-1	3.5	±0.20	kg·m ²
Effective thickness	BS EN 1849-1	3.5	±0.1	mm
Water tightness	BS EN 1928 (A)	Pass	-	2kPa passed
Water vapour resistance	BS EN 1931	> 6094	-	μ
Reaction to fire	BS EN 13501-1	Class E	-	-
Tensile strength	BS EN 12311-1	840 (MD); 550 (TD)	±20%	N/50 mm
Elongation	BS EN 12311-1	3.5 (MD); 3.8 (TD)	±0.5%	%
Dimensional stability	BS EN 1107-1	≤ 0.5	≥ 0.5	%
Flexibility at low temperature	BS EN 1109	≤ -10	≥ -10	°C
Flow resistance at elev. temp	BS EN 11071-1	≥ 90	-	90°C

MD = Machine Direction. TD = Transverse Direction.

PACKAGING

Description	Roll Dimensions	Rolls per pallet	Product Code
TorchSafe TA VCL Stripes	1m x 7.5m	25	10001442

STORAGE

Materials for reinforced bitumen membrane roofing should be stored upright on clean dry level surfaces, undercover and clear of the ground. The same protection should be given to materials temporarily kept outdoors or on the roof during construction. Storage temperatures should be between 0°C and 30°C. Refer to BS 8000-4 (Section 2.1.2.2) for further information.

INSTALLATION SUMMARY

TorchSafe TA VCL Stripes membranes are applied by heat-activated or self-adhesive application. The membrane is to be installed in accordance with current and relevant standards such as BS 8217, BS 6219, BS 6229 and BS 8000-4.

For further details please consult our Flat Roofing Product Installation Guidelines or contact our BMI Icopal technical services team.

TECHNICAL SERVICES

For further information and technical support, please contact our technical services team:

T: +44 (0) 330 123 4585

E: technical.uk@bmigroup.com

CERTIFICATION

TorchSafe TA VCL Stripes has been independently site and laboratory tested by the British Board of Agrément, and awarded BBA certificate number 09/4645 (PS4).



SAFETY, QUALITY & ENVIRONMENT

BMI Icopal membranes are manufactured under a Quality Management System approved to ISO 9001: 2015 and an Environmental Management System approved to ISO 14001: 2015, by TÜV NORD CERT GmbH.

Information regarding transportation, handling, storage and disposal can be found on the relevant Safety Data Sheet.



ISO 9001:2015
44 100 21410102



ISO 14001:2015
44 100 21410102



BMI Group UK Limited

BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW
bmigroup.com/uk

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact BMI Icopal technical services team.